



VOCE	A	B	L	G	a	D-Max		
						●	●	■
CT2A	11	14.5	53	M10X0.8	16°	7.5	6	5
CT4	16	21	58	M14X1.00	16°	10.5	9	7.5
CT4L	16	20.5	59	M14X1.00	16°	12	9.5	8
CT4B	18	21.8	59	M16X1.00	30°	13	11	9
CT5	22	29	68	M19X1.00	16°	16	14	11
CT5C	22	29	68	M22X1.00	16°	18	15	13
CT5A	24	30	61	M24X1.00	30°	16	14	11
CT6D	26	29	77	M25X1.00	16°	20	16	13
CT6S	28	34	82	M25X1.00	16°	21	18	15
CT6T	28	38	81	M25X1.00	30°	21	18	15
CT6	32	39.8	71	M32X1.00	30°	22	19	15
CT6A	34	41	87.5	M34X1.00	10°	25	21	17
CT7B	42	49	82	M40X1.00	16°	32	26	21
CT7S	48	54	82	M46X1.00	16°	38	-	-

LUNGHEZZA DELLA GUIDA IN METALLO DURO

Ø	X											
	Lg standard	Lg. media	Lg XL									
			CT4	CT4B	CT5A	CT5C	CT6A	CT6D	CT6S	CT6T	CT7B	CT7S
2-3	15 mm	30 mm										
4	18 mm	30 mm										
5-9	20 mm	30 mm										
10-15	22 mm	30 mm										
16-19	25 mm	30 mm										
20-24	27 mm	40 mm	35 mm (da Ø 2 a 8)	35 mm (da Ø 2 a 12)	35 mm (da Ø 2 a 16)	45 mm (da Ø 2 a 15)	60 mm (da Ø 5 a 26)	50 mm (da Ø 2 a 16)	55 mm (da Ø 2 a 20)	55 mm (da Ø 2 a 20)	55 mm (da Ø 5 a 32)	55 mm (da Ø 5 a 38)
25-26	28 mm	40 mm										
27	29 mm	40 mm										
28-29	30 mm	40 mm										
30-33	31 mm	40 mm										
33-38	33 mm	40 mm										